


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 16/01	A1	(11) International Publication Number: WO 97/14465 (43) International Publication Date: 24 April 1997 (24.04.97)
(21) International Application Number: PCT/SE96/01291 (22) International Filing Date: 10 October 1996 (10.10.96) (30) Priority Data: 9503614-1 16 October 1995 (16.10.95) SE (71) Applicant (for all designated States except US): LOUIS GIBECK AB [SE/SE]; P.O. Box 711, S-194 27 Upplands Väsby (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): LAMBERT, Hans [SE/SE]; Odengatan 43, S-113 51 Stockholm (SE). (74) Agents: KARLSSON, Leif et al.; L.A. Groth & Co. KB, P.O. Box 6107, S-102 32 Stockholm (SE).		(81) Designated States: AU, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: A DEVICE FOR RECOVERING ANAESTHETIC**(57) Abstract**

A device for recovering anaesthetic during the use of inhaled anaesthetics is connected to a patient and comprises an anaesthetic evaporator for supplying anaesthetic to the patient and an absorption filter for absorption and desorption of the medium. The device comprises a body (4) applied between the absorption filter (6; 16) and the patient (P), the gases breathed by the patient passing across said body and the anaesthetic evaporating on the surface thereof. The absorption filter is in the form of a flat element (6) applied in the flow path of the gas breathed by the patient and contains or consists of fibres of active carbon. Furthermore, the absorption filter is movably applied in a housing (5; 15) between a position in which substantially all the gases breathed pass through the filter and a position in which a small portion of the gases breathed passes through this.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Larvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

A DEVICE FOR RECOVERING ANAESTHETIC

Technical field:

5 The present invention relates to a device for recovering anaesthetic during the use of inhaled anaesthetics. The device is connected to a patient and comprises an anaesthetic evaporator for supplying anaesthetic to the patient and an absorption filter for absorption and desorption of the medium.

10 Background art:

A device of the type described above is disclosed through SE-B 459 155. The evaporator is arranged externally, i.e. the gas is conveyed to an opening in a collection tube between the patient and the absorption filter.

15

In the evaporator a fresh gas flow is conducted past the anaesthetic, in liquid phase, whereupon the medium evaporates in part of the fresh gas flow. This gas is mixed incompletely or unevenly with the gas breathed by the patient when it enters the tube since it enters through
20 said opening. Since the supply of anaesthetic is also affected both by the flow and pressure of the gas breathed by the patient, it is difficult to know how much anaesthetic is actually being supplied to the patient.

The absorption filter is in the form of a body or container holding
25 active carbon, for instance, in granular or powder form. Large quantities of such material are necessary for the absorption effect to be efficient. This means that the filter must be large and thus requires considerable space as well as increasing the quantity of carbon dioxide that is re-inhaled. The material must also be surrounded by a suitable
30 filter to prevent the granules/powder from flowing into the patient's lungs. The carbon also absorbs a certain amount of gas which therefore fails to benefit the patient. In some cases the breathing resistance may be considerable.

35 When using the device according to SE-B 459 155 it is impossible to abruptly alter or disconnected the supply of anaesthetic to the patient

since some medium remains in the absorption filter. The remaining medium is admittedly gradually aired out but this takes time and in the meanwhile the patient is receiving an undesired supply of anaesthetic.

- 5 Neither does the device according to SE-B 459 155 allow the supply of anaesthetic to be closed off should the patient temporarily stop breathing.

Description of the invention:

- 10 One object of the present invention is at least partially to eliminate the drawbacks of previously known devices of the type described above and to provide a device having one or more of the following advantages:

- Supply of anaesthetic to the gas breathed by the patient in
15 exact quantities and in such a manner that the consumption of anaesthetic can be accurately controlled.

- The absorption filter requires little volume and takes up little
space, in spite of breathing resistance being maintained or decreased.

- 20
- The absorption filter need not be surrounded by an extra filter.

- The supply of anaesthetic from the absorption filter to the
25 patient can be quickly cut off.

- The supply of anaesthetic from the evaporator to the patient
can be closed off if the patient stops breathing temporarily.

- 30 This object is fulfilled by the device according to the invention being given the features defined in the characterizing part of the claims.

Brief description of the drawings:

- Figure 1 is a schematic view from the side, partly in section, of one
35 embodiment of the invention according to the present invention, and

Figures 2 and 3 are schematic views from the side, partly in section, of a second embodiment of the device according to the present invention.

Figure 1 shows a container 1 containing anaesthetic with high vapour pressure and in liquid phase. A pump 2 is connected to the container 1 and supplies the liquid to an evaporator 4 via a tube 3 at a velocity that can be varied depending on the need for anaesthetic. The evaporator is applied inside a housing 5 which also contains an absorption-desorption filter 6. The evaporator comprises a body on the surface of which the anaesthetic fluid evaporates. This surface is preferably large in area. The body may be porous, for instance, with the inlet situated centrally in the body or it may be provided with flanges to distribute the anaesthetic uniformly.

One end of the housing 5 is preferably detachably connected to a respirator or the like, not shown, via a tube 7, and the other end of the housing is preferably detachably connected to a patient P via a tube 8. The gases breathed flow between the respirator and the patient in the direction of the arrows, also passing the evaporator 4 and the absorption filter 6. When the patient inhales, a predetermined quantity of anaesthetic will be supplied which, upon exhaling, will be partly deposited in the filter 6 and is therefore recovered to be inhaled again.

The absorption material in the filter 6 consists of active carbon in the form of fibres or bound to fibres woven to form fabric or wadding. The volume of the filter 6 is thus small since its efficiency per weight and volume unit is large which in turn means that the quantity of anaesthetic gas enclosed in the filter is small. Since the woven material forms a self-carrying unit, no extra carrier is necessary. The fabric can be shaped so that its breathing resistance is slight and it can be treated with bacteria-filtering means or be laminated with a bacteria filter.

The absorption filter 6 may be shaped as a thin disc, as shown in Figure 1, thus reducing the extension of the housing in the direction of the gases being breathed, to a minimum. If the housing 5 is made lower, the disc can be made rotatable in this, rotation being effected from the

outside of the housing by a knob, for instance (not shown). The disk then functions as a damper which, when active, assumes the position shown in Figure 1 in which all the gas breathed by the patient that flows through the housing also flows past the damper and, when most
5 inactive, is substantially in horizontal position. In the latter position the flow of anaesthetic from the filter 6 to the patient is minimized when the supply of anaesthetic to the evaporator 4 is cut off.

Figure 1 also shows a device for closing off the supply of anaesthetic should the patient temporarily stop breathing. The device comprises a
10 flow gauge 9 applied in a housing 5 which senses if the gas breathed is flowing to and/or from the patient. The flow gauge 9 is suitably applied between the evaporator 4 and the filter 6 but may instead be placed somewhere else in the housing 5 or in the tube 7 or 8. The
15 gauge 9 is connected to an electronic or mechanical converter 10 connected to a valve 11 in the tube 3. When the gauge 9 senses the existence of a gas flow the valve 11 is open and allows through anaesthetic, and when the gauge 9 senses that the gas flow has ceased for a certain period, the valve is closed via the converter 10. The gauge
20 9 may consist, for instance, of two pressure sensors, one on each side of a flow resistor or a thermistor which is cooled by the flow, or a propeller which senses the flow and then influences an optical cell.

Figure 2 shows a second embodiment of the casing containing the
25 evaporator and absorption filter. The housing, designated 15, is spherical and the absorption filter, designated 16, is in the form of a circular cylinder having its longitudinal axis parallel with the tubes 7 and 8 and in the position shown in Figure 2. The circular end edges of the cylinder 16 abut and seal against the inside of the housing 15.
30 A knob 17 on the outside of the housing 15 is connected to the cylinder 16. When the knob 17 is turned 90° the cylinder 16 assumes the position shown in Figure 3 so that the gases breathed can flow between the envelope surface of the cylinder and the inside of the housing. The cylinder 16 consists of a gas-tight outer casing and contains active
35 carbon in powder or granular form.

Although only a few embodiments of the device according to the invention have been described above and shown in the drawings it should be understood that the invention is not limited to these embodiments, but only by the limitations defined in the appended
5 claims.

CLAIM

1. A device for recovering anaesthetic during the use of inhaled anaesthetics, the device being connected to a patient and comprising an
5 anaesthetic evaporator for supplying anaesthetic to the patient and an absorption filter for absorption and desorption of the medium, characterized by a body (4) applied between the absorption filter (6; 16) and the patient, the gases breathed by the patient passing across said body and the anaesthetic evaporating on the surface thereof.
- 10 2. A device as claimed in claim 1, characterized in that the absorption filter (6; 16) and the body (4) across which the gases breathed by the patient flow are applied in a housing (5; 15) to which a container (1) holding anaesthetic in liquid phase is connected.
- 15 3. A device as claimed in claim 1 or 2, characterized in that the body (4) across which the gases breathed by the patient flow, has a large area and preferably consists of porous material to provide uniform distribution of the anaesthetic in the gas flow to the patient.
- 20 4. A device as claimed in claim 2 or 3, characterized in that the body (4) is porous and that the outlet of the anaesthetic container is located inside the body.
- 25 5. A device as claimed in claim 1, characterized in that the absorption filter (6; 16) is in the form of a flat element (6) applied in the flow path of the gas breathed by the patient and contains or consists of fibres of active carbon.
- 30 6. A device as claimed in claim 5, characterized in that the flat element (6) is woven.
7. A device as claimed in claim 5 or 6, characterized in that the flat element (6) comprises or is laminated with a bacteria
35 filter.

8. A device as claimed in claim 1, characterized in that the absorption filter (6; 16) is movably applied in a housing (5; 15) between a position in which substantially all the gases breathed pass through the filter and a position in which a small portion of the gases
5 breathed passes through this.

9. A device as claimed in claim 8, characterized in that the absorption filter (6; 16) can be rotated with the aid of a turning element (17) on the outside of the housing.

10


10. A device as claimed in claim 8 or 9, characterized in that the absorption filter (6; 16) is in the form of a cylinder (16) and the housing (5; 15) is in the form of a substantially spherical container (15), whereby in a first position the cylinder seals against the inside of
15 the container and in a second position it is spaced from the inside of the container.

11. A device as claimed in claim 9, characterized in that the absorption filter (6; 16) is in the form of a thin, circular disc (6), whereby in a first position the periphery of the disc seals against the
20 inside of the housing (5; 15) and in a second position the main plane of the disc is substantially parallel with the direction of flow of the gases breathed.

12. A device as claimed in any of the preceding claims, characterized in that a sensor (9) is arranged in the housing (5; 15) or in a tube (7, 8) connected thereto, to sense the pressure, flow and/or velocity of the gas flow and to close the supply of anaesthetic to the evaporator when the gas flow has ceased for a certain period of
25 30 time.

1 / 2

Fig. 1



2 / 2

Fig. 2





Fig. 3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/01291

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61M 16/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	SE 467996 B (SIEMENS-ELEMA AB), 19 October 1992 (19.10.92) --	1-12
A	GB 2255912 A (DRÄGERWERK AKTIENGESELLSCHAFT), 25 November 1992 (25.11.92) --	1-12
A	SE 459155 B (ZENOVA AB), 12 June 1989 (12.06.89) -- -----	1-12

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

9 January 1997

Date of mailing of the international search report

01 -02- 1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Christer Jönsson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

28/10/96

International application No.
PCT/SE 96/01291

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
SE-B- 467996	19/10/92	AU-B- 648549 DE-D,T- 69107451 EP-A- 0496336 EP-A,B- 0523107 SE-T3- 0523107 EP-A- 0720858 JP-A- 4317660 SE-A- 9100228 US-A- 5237990 US-A- 5423787	28/04/94 14/06/95 29/07/92 20/01/93 10/07/96 09/11/92 26/07/92 24/08/93 13/06/95
GB-A- 2255912	25/11/92	DE-A- 4116512 FR-A- 2676651	26/11/92 27/11/92
SE-B- 459155	12/06/89	DE-A- 3874737 EP-A,B- 0359755 JP-T- 3500488 SE-A- 8701547 US-A- 5044361 WO-A- 8807876	22/10/92 28/03/90 07/02/91 15/10/88 03/09/91 20/10/88